



UTV Pre-Ride Inspection Checklist

A. What to do before starting the engine key (Key off)	
Check wheels for damage and for abnormal play. Make sure the lug nuts are tight. Refer to wheels and tires maintenance procedures for torque specifications.	
Check cleanliness of the radiator	
Inspect front grill kit for cleanliness	
Check engine oil level	
Check coolant level	
Check brake fluid level	
Inspect the engine air filter, clean, or replace it if needed	
Inspect and clean the CVT air filter	
Check drive shaft boots and protectors' condition	
Cargo Load: if you transport cargo, respect the maximum loading capacity. Refer to loading the cargo box. Ensure cargo is properly secured to the rear cargo box.	
Vehicle Load: Ensure that total load on the vehicle does not exceed specifications. Refer to carry loads	
If you are pulling a trailer or another equipment: -Check hitch and trailer ball condition -Respect the tongue capacity and towing capacity as indicated on the label affixed to the hitch or refer to specifications -Ensure trailer is properly secured to hitch	
Check if the cargo box is properly latched	
Check underneath vehicle for any debris on chassis or suspension and clean them properly	

B. What to do before starting the engine (Key On)	
Check operations indicator lamps in gauge (during first few second of key being on)	
Check for messages in gauge	
Check for operation and cleanliness of headlights and taillights	
Check operation of high and low beam lights	
Check operation of brake lights	
Check if seat belt symbol operates properly when belts are latched/unlatched	
Check side nets for any damage. Have the nets replaced if any damage is found. Fasten all side nets and confirm that they latch securely. Use the adjustment strap to tighten the nets.	
Check seat belts for any damage. Fasten all seat belts and confirm that they latch securely	
Press on the accelerator pedal a few times to ensure it operates freely and it returns to the rest position when released	
Press down on the brake pedal a few times and make sure you feel firm resistance and then that it fully returns to the rest position when released	
Check the fuel level	



UTV Pre-Ride Inspection Checklist

c. What to do after the engine is started	
Check if steering wheel operates freely by completely turning it from side to side.	
Turn the ignition switch to off to verify if the engine shuts down and then restart engine	
Check operations of shift lever (P, R, N, H, and L)	
Check operation of 2WD and 4WD selector	
Drive forward slowly a few feet and apply the brake. The brake pedal must feel firm when it is applied. The pedal must return to the resting position when released. The brakes must respond adequately to the driver's input.	

Name

Date