

SAFETY DATA SHEET

1. Identification

Product number 10000028754
Product identifier 11 OZ NAPA MAC'S OPEN GEAR LUBE 1366
Revision date 09-29-2016
Company information NAPA Balkamp
2601 Stout Heritage Parkway
Plainfield, IN 46168 United States
Company phone General Assistance 1-317-754-3900
Emergency telephone US 1-866-836-8855
Emergency telephone outside US 1-952-852-4646
Version # 02
Supersedes date 06-17-2016
Recommended use LUBRICANT
Recommended restrictions None known.

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1
Health hazards Acute toxicity, inhalation Category 4
Skin corrosion/irritation Category 2
Reproductive toxicity (fertility, the unborn child) Category 2
Aspiration hazard Category 1
OSHA defined hazards Not classified.

Label elements



Signal word

Danger

Hazard statement

Extremely flammable aerosol. May be fatal if swallowed and enters airways.
Harmful if inhaled. Suspected of damaging the unborn child. Suspected of

Precautionary statement

Hazard(s) not otherwise classified (HNOC) Combustible.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number
Distillates (Petroleum), Hydrotreated Light		64742-47-8
Asphalt		8052-42-4
Acetone		67-64-1
Butane		106-97-8
Heptane, branched, cyclic and linear		426260-76-6
Propane		74-98-6
Cyclohexane		110-82-7
n-Heptane		142-82-5
n-Hexane		110-54-3
Toluene		108-88-3

Other components below reportable levels

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Administer artificial respiration if needed. Call a POISON CENTER or doctor/physician for further advice.

Skin contact

Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs, get medical advice/attention. Wash contaminated clothing before reuse.

Eye contact

Rinse with water. Get medical attention if irritation develops and persists.

Ingestion

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting unless instructed. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and delayed

Aspiration may cause pulmonary edema and pneumonitis. Skin irritation. Mouth pain.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information

IF exposed or concerned: Get medical advice/attention. If you feel unwell, show this label where possible. Ensure that medical personnel are aware of the product involved, and take precautions to protect themselves. Show this safety data sheet to the attending physician.

US. ACGIH Threshold Limit Values

Components	Type	Value	For
Asphalt (CAS 8052-42-4)	TWA	0.5 mg/m ³	Inh
Butane (CAS 106-97-8)	STEL	1000 ppm	
Cyclohexane (CAS 110-82-7)	TWA	100 ppm	
n-Heptane (CAS 142-82-5)	STEL	500 ppm	
	TWA	400 ppm	
n-Hexane (CAS 110-54-3)	TWA	50 ppm	
Toluene (CAS 108-88-3)	TWA	20 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	For
Acetone (CAS 67-64-1)	TWA	590 mg/m ³ 250 ppm	
Asphalt (CAS 8052-42-4)	Ceiling	5 mg/m ³	Fu
Butane (CAS 106-97-8)	TWA	1900 mg/m ³ 800 ppm	
Cyclohexane (CAS 110-82-7)	TWA	1050 mg/m ³ 300 ppm	
n-Heptane (CAS 142-82-5)	Ceiling	1800 mg/m ³ 440 ppm	
	TWA	350 mg/m ³ 85 ppm	
n-Hexane (CAS 110-54-3)	TWA	180 mg/m ³ 50 ppm	
Propane (CAS 74-98-6)	TWA	1800 mg/m ³ 1000 ppm	
Toluene (CAS 108-88-3)	STEL	560 mg/m ³ 150 ppm	
	TWA	375 mg/m ³ 100 ppm	

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	25 mg/l	Acetone	Urine	*
n-Hexane (CAS 110-54-3)	0.4 mg/l	2,5-Hexanedion, without hydrolysis	Urine	*
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*

Individual protection measures, such as personal protective equipment

Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin protection	
Hand protection	Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.
Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.
Respiratory protection	If permissible levels are exceeded use NIOSH mechanical filter / organic vapor respirator or air-supplied respirator.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Observe any medical surveillance requirements. When using do not smoke, eat, drink, or use personal hygiene measures, such as washing after handling the material and before drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state	Gas.
Form	Aerosol.
Color	Not available.
Odor	Not available.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	520.62 °F (271.46 °C) estimated
Flash point	-156.0 °F (-104.4 °C) PROPELLANT estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower (%)	1.3 % estimated
Flammability limit - upper (%)	9.6 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.

Vapor pressure 30 psig @70F estimated

Vapor density Not available.

Relative density (air = 1) Not available.

VOC (Weight %) 24.5 % estimated

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous reactions Hazardous polymerization does not occur.

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Acids. Strong oxidizing agents.

Hazardous decomposition products No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Harmful if inhaled.

Skin contact Causes skin irritation.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Droplets of the product aspirated into the lungs through ingestion or vomiting may cause chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics Aspiration may cause pulmonary edema and pneumonitis. Skin irritation. Mouth pain.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways. Harmful if inhaled.

Components	Species	Test Results
Acetone (CAS 67-64-1)		
<u>Acute</u>		
Dermal		
LD50	Guinea pig	> 7426 mg/kg, 24 Hours > 9.4 ml/kg, 24 Hours
	Rabbit	> 7426 mg/kg, 24 Hours > 9.4 ml/kg, 24 Hours
Inhalation		
LC50	Rat	55700 ppm, 3 Hours 132 mg/l, 3 Hours 50.1 mg/l
Oral		
LD50	Rat	5000 mg/kg

Components	Species	Test Results
Cyclohexane (CAS 110-82-7)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Inhalation		
LC50	Rat	> 32880 mg/m ³ , 4 Hours > 5540 ppm, 4 Hours
Oral		
LD50	Rabbit	> 5000 mg/kg
	Rat	> 5000 mg/kg
Distillates (Petroleum), Hydrotreated Light (CAS 64742-47-8)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 2000 mg/kg > 2000 mg/kg, 24 Hours
Inhalation		
LC50	Rat	> 7.5 mg/l, 6 Hours > 4.6 mg/l, 4 Hours
Oral		
LD50	Rat	> 5000 mg/kg
n-Heptane (CAS 142-82-5)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 2000 mg/kg, 24 Hours
Inhalation		
LC50	Rat	> 29.29 mg/l, 4 Hours
Oral		
LD50	Rat	> 5000 mg/kg
n-Hexane (CAS 110-54-3)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 2000 mg/kg, 4 Hours > 5 ml/kg, 4 Hours
Inhalation		
LC50	Rat	> 5000 ppm, 24 Hours

Components	Species	Test Results
Toluene (CAS 108-88-3)		
Acute		
Dermal		
LD50	Rabbit	> 5000 mg/kg, 24 H
Inhalation		
LC50	Mouse	6405 - 7436 ppm, 6 5320 ppm, 8 Hours
	Rat	5879 - 6281 ppm, 6 25.7 mg/l, 4 Hours
Oral		
LD50	Rat	> 5000 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.
Respiratory or skin sensitization	
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater mutagenic or genotoxic.
Carcinogenicity	Risk of cancer cannot be excluded with prolonged exposure.
IARC Monographs. Overall Evaluation of Carcinogenicity	
Asphalt (CAS 8052-42-4)	2B Possibly carcinogenic to humans.
Toluene (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to hu
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)	
Not regulated.	
US. National Toxicology Program (NTP) Report on Carcinogens	
Not listed.	
Reproductive toxicity	Suspected of damaging fertility. Suspected of damaging the unborn child.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	May be fatal if swallowed and enters airways.
Chronic effects	Prolonged exposure may cause chronic effects.

Components			Species	Test Results
n-Heptane (CAS 142-82-5)				
Aquatic				
Fish	LC50		Mozambique tilapia (Tilapia mossambica)	375 mg/l, 96 hours
n-Hexane (CAS 110-54-3)				
Aquatic				
Fish	LC50		Fathead minnow (Pimephales promelas)	2.101 - 2.981 mg/l, 96 hours
Toluene (CAS 108-88-3)				
Aquatic				
Algae	IC50		Algae	433.0001 mg/L, 72 hours
Crustacea	EC50		Daphnia	7.645 mg/L, 48 hours
			Water flea (Daphnia magna)	5.46 - 9.83 mg/l, 48 hours
Fish	LC50		Coho salmon,silver salmon (Oncorhynchus kisutch)	8.11 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Acetone	-0.24
Butane	2.89
Cyclohexane	3.44
n-Heptane	4.66
n-Hexane	3.9
Propane	2.36
Toluene	2.73

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical potential, endocrine disruption, global warming potential) are expected from this product.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not empty into drains. Do not dispose under pressure. Do not puncture, incinerate or crush. Do not allow this material to enter sewers/water supplies. Do not contaminate ponds, waterways or ditches with this material. Do not use empty container. Dispose of contents/container in accordance with local/regional/national regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the disposal company.

Waste management code Dispose of in accordance with local regulations. Empty containers and lines

Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed.

IATA

UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	Yes
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.
Packaging Exceptions	LTD QTY


IMDG

UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	Yes
EmS	F-D, S-U
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Packaging Exceptions	LTD QTY
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.

IATA; IMDG



Marine pollutant



General information

DOT Regulated Marine Pollutant. IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard C Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1)

Listed.

Cyclohexane (CAS 110-82-7)

Listed.

n-Hexane (CAS 110-54-3)

Listed.

Toluene (CAS 108-88-3)

Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes

Delayed Hazard - Yes

Fire Hazard - Yes

Pressure Hazard - Yes

Reactivity Hazard - No

Safe Drinking Water Act (SDWA) Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.02(c))
Chemical Code Number

Acetone (CAS 67-64-1) 6532
Toluene (CAS 108-88-3) 6594

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12)

Acetone (CAS 67-64-1) 35 %WV
Toluene (CAS 108-88-3) 35 %WV

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1) 6532
Toluene (CAS 108-88-3) 594

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code 11360-11365)
Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, title 26, section 88000)
(a)

Acetone (CAS 67-64-1)
Asphalt (CAS 8052-42-4)
Butane (CAS 106-97-8)
n-Hexane (CAS 110-54-3)
Toluene (CAS 108-88-3)

US. Massachusetts RTK - Substance List

Acetone (CAS 67-64-1)
Asphalt (CAS 8052-42-4)
Butane (CAS 106-97-8)
Cyclohexane (CAS 110-82-7)
n-Heptane (CAS 142-82-5)
n-Hexane (CAS 110-54-3)
Propane (CAS 74-98-6)
Toluene (CAS 108-88-3)

US. New Jersey Worker and Community Right-to-Know Act

Acetone (CAS 67-64-1)
Asphalt (CAS 8052-42-4)
Butane (CAS 106-97-8)
Cyclohexane (CAS 110-82-7)
n-Heptane (CAS 142-82-5)
n-Hexane (CAS 110-54-3)
Propane (CAS 74-98-6)
Toluene (CAS 108-88-3)

US. Pennsylvania Worker and Community Right-to-Know Law

Acetone (CAS 67-64-1)
Asphalt (CAS 8052-42-4)
Butane (CAS 106-97-8)

International Inventories

Country(s) or region	Inventory name
Australia	Australian Inventory of Chemical Substances (AICS)
Canada	Domestic Substances List (DSL)
Canada	Non-Domestic Substances List (NDSL)
China	Inventory of Existing Chemical Substances in China (IECSC)
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)
Europe	European List of Notified Chemical Substances (ELINCS)
Japan	Inventory of Existing and New Chemical Substances (ENCS)
Korea	Existing Chemicals List (ECL)
New Zealand	New Zealand Inventory
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the government of the country(s).
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the government of the country(s).

16. Other information, including date of preparation or last revision

Issue date	06-17-2016
Revision date	09-29-2016
Version #	02
Disclaimer	We cannot anticipate all conditions under which this information and its product, or other manufacturers in combination with its product, may be used. It is the responsibility of the user to ensure safe conditions for handling, storage and disposal of the product, and to avoid loss, injury, damage or expense due to improper use. The information in this document is based on the best knowledge and experience currently available.
Revision information	This document has undergone significant changes and should be reviewed